

---

**PRODUCT INFORMATION**

---



## **Finishfit® OIL High Gloss 1667**

---

**FIELD OF APPLICATION**

---

Finishfit® OIL High Gloss 1667 is an universal oil-based varnish for processing in the printing unit. It is suitable for absorbent substrates and achieves a glossy finish.

---

**PROPERTIES**

---

- Support of the matt/gloss contrast
- Gloss ≈ 68 gloss point at 2 g/m<sup>2</sup> coating application (laboratory print)
- Cobalt-free
- Suitable for perfecting printing
- Low yellowing
- Very good film formation
- Very good rub resistance
- Excellent stacking behavior
- Slow setting
- Slow drying time
- Can be used wet in wet and wet on dry
- Problem-free processing with and without fountain solution
- Not suitable for use on food contact material (FCM)

---

### APPLICATION

---

- Always read the label and product information before use
- The properties depend on the substrate and application quantity
- Stir well before use
- Light use of an IR drier allows faster processing

---

### ADDITIVES

---

- Cleanfit Roller Paste 2299
- Washfit All AF 2232
- Powderfit Medium 2135 or Powderfit Medium 2136

---

### STORAGE

---

- Protect from frost, heat and direct sun light
- Storage only in original packaging at 10 – 30 °C (50 – 86 °F)
- Unopened and correctly stored it has a shelf life of 24 months from delivery date

---

### STANDARD PACKAGING

---

2,5 kg tin

200 kg barrel

Note: This technical description is intended to inform and advise you. It corresponds to our current state of knowledge. However, since the specific application depends on a number of factors over which we have no influence, no guarantee and liability for the pressure failure can be derived.