
PRODUCT INFORMATION



Finishfit® OIL Matt Effect 1578

FIELD OF APPLICATION

Finishfit® OIL Matt Effect 1578 has been specially designed to achieve matt-gloss effects in combination with UV coating or dispersion varnishes. It is processed in the printing unit like a conventional print varnish. The areas that are to appear matt in the finished product are overprinted with Finishfit® OIL Matt Effect 1578, the UV or dispersion varnish is applied inline directly after the effect varnish and dried with a UV or IR dryer. Depending on the amount of effect varnish applied, the matting effect is stronger or weaker.

PROPERTIES

- Very good on printed products with ink content to show the matt-gloss effect
- Yellowing of the white paper surfaces is reduced to a minimum by this varnish, even after a longer period of time
- Problem-free processing with and without fountain solution
- Can be used on paper and cardboard

APPLICATION

- Always read the label and the product information before use
- The properties depend on the substrate and the application quantity
- Stir well before use

ADDITIVES

- For cleaning rubber rollers we recommend Cleanfit Rollerpaste 2299
- For cleaning in automatic washing systems we recommend Washfit AIII 2232
- Powder spraying if required

STORAGE

- Protect from frost, heat and direct sunlight
- Storage only in original packaging at 10 – 30 °C (50 – 86° F)
- Unopened and correctly stored Finishfit® OIL Matt Effect 1578 has a shelf life of 12 months from delivery date

STANDARD PACKAGING

- 1,0 kg tin
- 2,5 kg tin
- 200 kg drum

Note: This technical description is intended to inform and advise you. It corresponds to our current state of knowledge. However, since the specific application depends on a number of factors over which we have no influence, no guarantee and liability for the pressure failure can be derived.