

---

**PRODUCT INFORMATION**

---



## **Finishfit® WBC High Gloss Cigarette FCM 1960**

---

**FIELD OF APPLICATION**

---

Finishfit® WBC High Gloss Cigarette FCM 1960 is recommended for inline coating in sheetfed offset/coating unit (chambered doctor blade). The varnish is also suitable for off-line coating with dry, conventional inks. In both cases, it can be used over a large area without water.

Finishfit® WBC High Gloss Cigarette FCM 1960 is also suitable for the use on the side of a print product facing away from the foodstuff, which should meet the requirements of Regulation (EG) 1935/2004, Art. 3.

Finishfit® WBC High Gloss Cigarette FCM 1960 has been specially developed for maximum machine speed with minimum transfer times between printing and finishing.

---

**PROPERTIES**

---

- Suitable for indirect food contact
- Especially for cigarette packaging 2-EH reduced
- Good heat resistance
- Low friction
- Drying by IR and hot air
- Excellent rub resistance
- Very good wet-blocking resistance
- Slow drying
- Glueable, foil embossable and UV-varnishable
- Applicable on one side only
- Can be used on paper and cardboard
- Standard viscosity 120 sec., measured at 20 °C (68° F), DIN 4mm viscosity cup

---

## APPLICATION

---

- Stir well before use
- The properties depend on the substrate and the application quantity
- Powder spraying if required

---

## ADDITIVES

---

- For cleaning flexo engraved rollers we recommend Cleanfit Anilox 2259

---

## STORAGE

---

- Protect from frost, heat and direct sunlight
- Storage only in original packaging at 10 – 30 °C (50 – 86°F)
- Unopened and correctly stored Finishfit® WBC High Gloss Cigarette FCM 1960 has a shelf life of 12 months from date of delivery

---

## STANDARD PACKAGING

---

- 25 kg can
- 220 kg drum
- 1.050 kg container/ IBC

Note: This technical description is intended to inform and advise you. It corresponds to our current state of knowledge. However, since the specific application depends on a number of factors over which we have no influence, no guarantee and liability for the pressure failure can be derived.