

---

**PRODUCT INFORMATION**

---

## **Finishfit Neutral 1998**

Dispersion Varnish

---

**PROPERTIES**

---

- Suitable for printing substrates with less than 100 g/m<sup>2</sup>
- Very low curl (anti curling)
- Drying by IR and hot air
- Rub resistant
- Wet blocking resistant
- Stress-relieved
- Fast drying
- Suitable for both-sided coating
- Suitable for short and long delivery
- Suitable for paper and cardboard
- Standard viscosity 35 – 50 sec. (deviant viscosity available on demand)
- Suitable for the indirect contact with foodstuff

---

**APPLICATION NOTES**

---

- The properties are depending on the printing substrate and applied quantity.
- Stir well before using.
- Use only printing inks which meet all fastness standards according to DIN 16524
- Protect against frost, heat and direct sunlight.
- Storage only in original packaging at 10° - 30°C.
- Viscosity measured at 20°C (68°F) with a viscosity cup DIN 4mm

---

**STORAGE / HANDLING**

---

Unopened and correctly stored the varnish Finishfit 1998 has a shelf-life time of 12 months from date of delivery.

This technical instruction sheet is designed for your information and reference. It is based on and conforms to our current knowledge. However as actual application is affected by many factors over which we have no control, we are not liable for printing failures.