

---

PRODUCT INFORMATION

---

## Waterfit sf if sn 2328

Fountain solution for printing IPA-free in sheetfed with semi neutral pH

---

FIELD OF APPLICATION

---

- Fast and clean start-ups
- For IPA free printing
- Clean circulation tank
- Improved drying of inks
- Reduced ink and paper piling
- Minimised kaolin build-up
- Prevents calcium deposits on rollers and blankets

---

PROPERTIES

---

- Corrosion inhibited
- Also for continuous stationary offset presses
- Excellent plate activation
- Stable ink water balance
- Controlled water pickup by the ink
- Minimised kaolin and calcium build-up
- Wide latitude dosage
- Semi neutral pH level

---

APPLICATION

---

Before adding the new fountain solution, it is important to empty and clean the circulation system. Also the condition of the dampening system is important. Check whether the dosing equipment is accurate and applies the correct dosage. For a precise control conductivity measurements are recommended. It is advisable to check the roller settings of the dampening system. When reducing or eliminating IPA a looser roller setting could be necessary.

---

SPECIFICATIONS

---

- Standard dosage (%): 4 - 5
- Increased conductivity ( $\mu\text{S}/\text{cm} / \%$ ): 330
- PH level: 5,4 - 5,8
- Specific density (kg/l): 1,03
- VOC content (% (Dir 1999/13/EC)): 15 - 25
- For medium hard water

---

CORRESPONDING PRODUCTS

---

<b>Extrafit System Clean</b>	Effective cleaner for fountain circulation system with minimum workload
<b>Extrafit Hardener</b>	Calcium free and OEM approved re-hardener for stable print quality
<b>Extrafit Damp Cleaner</b>	Efficient water-based dampening roller cleaner meeting the standards of BG ETEM
<b>Extrafit Roller Gel</b>	Gelbased calcium remover with strong cleaning power
<b>Washfit</b>	Excellent wash to reduce paper waster and to realise short washing times

---

STANDARD PACKAGING

---

- 20 KG
- 210 KG
- 1.050 KG

Note: This technical description is intended to inform and advise you. It corresponds to our current state of knowledge. However, since the specific application depends on a number of factors over which we have no influence, no guarantee and liability for the pressure failure can be derived.