

PRODUCT INFORMATION

Waterfit sf ir FCM 2213

Fountain solution for printing IPA-reduced in sheetfed

FIELD OF APPLICATION

- Reduced paper waste on restart
- Fast and clean start-ups
- Low consumption
- For IPA reduced printing

- Low hazardous classification
- · Reduced ink and paper piling
- Minimised kaolin build-up
- Prevents calcium deposits on rollers and blankets

PROPERTIES

- OEM approved
- Certificate of compliance for indirect food contact
- Also for continuous stationary offset presses
- Effective plate preservation

- Stable ink water balance
- Controlled water pickup by the ink
- UV/LED-UV ink compatible
- Maximum IPA reduction

APPLICATION

Before adding the new fountain solution, it is important to empty and clean the circulation system. Also the condition of the dampening system is important. Check whether the dosing equipment is accurate and applies the correct dosage. For a precise control conductivity measurements are recommended. It is advisable to check the roller settings of the dampening system. When reducing or eliminating IPA a looser roller setting could be necessary.

SPECIFICATIONS

• Standard dosage (%): 2 -3

Increased conductivity (µS/cm / %): 392

• PH level: 4,8 - 5,2

Specific density (kg/l): 1,07
VOC content (% (Dir 1999/13/EC)): 15 - 25

For medium hard water

CORRESPONDING PRODUCTS

Extrafit System Clean Extrafit Hardener

Effective cleaner for fountain circulation system with minimum workload Calcium free and OEM approved re-hardener for stable print quality

Extrafit Damp Cleaner Extrafit Roller Gel

Efficient water-based dampening roller cleaner meeting the standards of BG ETEM

Gelbased calcium remover with strong cleaning power

Washfit Excellent wash to reduce paper waster and to realise short washing times

STANDARD PACKAGING

• 20 KG • 210 KG • 1.050 KG

Note: This technical description is intended to inform and advise you. It corresponds to our current state of knowledge. However, since the specific application depends on a number of factors over which we have no influence, no guarantee and liability for the pressure failure can be derived.