

---

PRODUCT INFORMATION

---

## Waterfit sf ir FCM 2230

Fountain solution for printing with conventional IPA level in sheetfed

---

FIELD OF APPLICATION

---

- Immediate high-density copies
- Low consumption
- Low hazardous classification
- Clean circulation tank
- Eliminates window framing
- Minimised kaolin build-up
- Prevents calcium deposits on rollers and blankets

---

PROPERTIES

---

- OEM approved
- Corrosion inhibited
- Certificate of compliance for indirect food contact
- Also for continuous stationary offset presses
- Effective plate preservation
- Stable ink water balance
- Low water settings
- Conventional IPA usage

---

APPLICATION

---

Before adding the new fountain solution, it is important to empty and clean the circulation system. Also the condition of the dampening system is important. Check whether the dosing equipment is accurate and applies the correct dosage. For a precise control conductivity measurements are recommended. It is advisable to check the roller settings of the dampening system. When reducing or eliminating IPA a looser roller setting could be necessary.

---

SPECIFICATIONS

---

- Standard dosage (%): 2
- Increased conductivity ( $\mu\text{S}/\text{cm} / \%$ ): 510
- PH level: 4,8 - 5,2
- Specific density (kg/l): 1,9
- VOC content (% (Dir 1999/13/EC)): <1
- For medium hard water

---

CORRESPONDING PRODUCTS

---

<b>Extrafit System Clean</b>	Effective cleaner for fountain circulation system with minimum workload
<b>Extrafit Hardener</b>	Calcium free and OEM approved re-hardener for stable print quality
<b>Extrafit Damp Cleaner</b>	Efficient water-based dampening roller cleaner meeting the standards of BG ETEM
<b>Extrafit Roller Gel</b>	Gelbased calcium remover with strong cleaning power
<b>Washfit</b>	Excellent wash to reduce paper waster and to realise short washing times

---

STANDARD PACKAGING

---

- 20 KG
- 210 KG
- 1.050 KG

Note: This technical description is intended to inform and advise you. It corresponds to our current state of knowledge. However, since the specific application depends on a number of factors over which we have no influence, no guarantee and liability for the pressure failure can be derived.